



Email: admin@baldwinboats.com.au Website: https://www.baldwinboats.com.au 19 Etiwanda Ave Mildura VIC 3500



300R

POA

Specifications

Boat Details

PricePOABoat BrandMercuryModel300RLength0.00Year2024CategoryBoat Engines and Outboards

Hull Style-Hull Type-Power Type-Stock Number0

ConditionNewStateVictoriaSuburbMILDURAEngine MakeMercury

Description

The 300R FourStroke is the highest performing engine in its class. The naturally aspirated 4.6L V-8 provides an astounding 44% in increased displacement and up to 40% higher overall bottom end torque than the legacy two-stroke 300XS it replaces. Custom Racing intake cam profiles and short intake manifold runners maximise power throughout the rated speed range. An integrated oil cooler keeps oil temps down throughout the Racing exclusive 5800-6400 rpm operating range. Transient spark calibration boosts torque by 7% for unmatched acceleration. Advanced Range

Disclaimer

Our company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his agents and/or surveyors to investigate such details buyer desires validated. This vessel is offered subject to prior sale, price change or withdrawal without notice.



Phone: 0350227596

Email: admin@baldwinboats.com.au Website: https://www.baldwinboats.com.au

19 Etiwanda Ave Mildura VIC 3500

Optimisation (ARO) automatically adjusts fuel delivery for up to 10% improvement in cruise-speed fuel efficiency. All of this on regular 91-RON Unleaded fuel. Spesification RATED HORSEPOWER (HP/KW)300/224BORE & STROKE (IN/MM)3.6 X 3.4/92 x 86IDLE RPM600MAX RPM AT FULL THROTTLE5800-6400CYLINDERS/ENGINE CONFIGURATIONV-8 (64 degree) with 32-valve Dual Overhead Cam (DOHC)DISPLACEMENT (LITER/CID)4.6/279 INDUCTION SYSTEMCustom Racing Short-Runner Intake Manifold FUEL SYSTEME lectronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization FUEL REQUIREMENTS Unleaded Regular 87 Octane Minimum (R+M/2) or 90 RON 10% Ethanol Maximum IGNITION SYSTEM Smart Craft PCM 112 Digital Inductive CHARGING SYSTEM85-amp (1071 Watt) with idle Charge STARTING Electric Start with SmartStart Protection LUBRICATION SYSTEM Integrated wet sumpoll REQUIREMENTNMMA Certified FCW SAE 10W-30THROTTLE AND SHIFT CONTROLS Mechanical and Digital Throttle and Shift (DTS)TRI-RAM MIDSECTION High-Durometer Elastomer Upper Mount and Solid Lower Mounts HEAVY DUTY MIDSECTION Solid Mounts; Remote Trim System GEARCASE Torque Master, Sport Master or 5.44" HDGEAR RATIO1.75:1CAMBERED SKEGSport Master and Torque Master GEAR SHIFTF-N-RDRY WEIGHT (LBS./KG)L - 20"Std: 512/232; HD: 546/247XL - 25"556/252XXL - 30"566/257 WARRANTY3-Year Warranty

Engine Details

Engine Make

Mercury